

Item			5MP AHD / TVI / CVI / 960H / IP Hybrid DVR (w/ sensor alarm)			
모델명			IQ-QH04		IQ-QH08	IQ-QH16
Video Input Format			AHD,TVI(up to 5MP), CVI (up to 4MP), 960H, IP			
Video & Audio						
Video System			NTSC/PAL			
Video Input	BNC		4 inputs	8 inputs		16 inputs
	BNC & IP		Up to 6 Channels (BNC x4 + IP x2)	Up to 12 Channels (BNC x8 + IP x4)		Up to 24 Channels (BNC x16 + IP x8)
	IP Only		6 inputs	12 inputs		8 inputs
Video Output			1 VGA(up to 1080P) and 1 HDMI(4CH 1080P, 8CH & 16CH up to 4K) output			
Audio input / output (RCA)			4 inputs / 1 output	8 inputs / 1 output		16 inputs / 1 output
Recording						
Video Compression			H.264			
Analog	Recroding Resolutiion		2592X1944(5MP), 2592x1520(4MP), 2048x1536(3MP), 1920x1080(1080P), 1280x720(720P), 960x480(960H)			
	Recoding Frame Rate While in Live View (Per Channel)	5MP	PAL/NTSC: 10fps	PAL/NTSC: 12fps		PAL/NTSC: 11fps
		4MP	PAL/NTSC: 15fps			
		3MP	PAL/NTSC: 20fps			
		2MP(1080P)	PAL: 25fps / NTSC: 30fps			
		1MP(720P)	PAL: 25fps / NTSC: 30fps			
		960H	PAL: 25fps / NSTC: 30fps			
IP	IP Camera Support		4MP / 3MP / 2MP(1080P) / 1M(720P) / 960H			
	Recoding Frame Rate		(Per Channel) PAL:25fps NTSC: 30fps			
	Input Bandwidth		16Mbps~48Mbps	32Mbps~96Mbps		64Mbps
	Max. Output Bandwidth		32Mbps	64Mbps		128Mbps
	Peak Decode Performance		2CHs realtime @4MP 4CHs realtime @1080P	4CHs realtime @4MP 8CHs realtime @1080P		8CHs realtime @4MP 16CHs realtime @1080P
Recording Mode			Continuous / Manual / Schedule / Motion Detection / Sensor Triggered			
HDD Supported			1 SATA HDD, up to 6TB	2 SATA HDDs, up to 12TB		2 SATA HDDs, up to 12TB
Network						
Network Interface			RJ45, 10M/100M			
Network Type			Static IP, DHCP, PPPoE, 3G			
Web Surveillance Support			IE / Firefox / Google Chrome / Mac Safari			
Mobile App Support			iOS & Android APP: RxCamView			
Playback & Backup						
Local Playback Simultaneously			Max. 4 Channels	Max. 8 Channels		Max. 16 Channels
Remote Playback via Network			Max. 4 Channels Simultaneously via CMS, IE/Mac Safari or Mobile App			
Backup Method			USB, Network, e-SATA (Optional)			
General						
USB			USB2.0 x2	USB3.0 x1, USB2.0 x1		USB3.0 x1, USB2.0 x1
PTZ Control			Yes, built-in RS485 & Coaxial Protocol (UTC)			
Sensor & Alarm Port			4 inputs / 1 output	8 inputs / 1 output		16 inputs / 1 output
Power Supply			DC 12V/2A	DC 12V/5A		DC 12V/5A
Dimension(WxDxH)			300X227X53mm	378x340x50mm		378x340x50mm
Working Environment			-10℃~+55℃ / 10%~90%RH			

