

SPEED DOME CAMERA



- ① SONY STARVIS IMAGE SENSOR
- ② AHD/TVI/CVI/CVBS 선택가능
- ③ 무손실 & REAL TIME 비디오 전송
- ④ FULL HD1080P, 20x / 36x ZOOM
- ⑤ UTC & RS-485 지원
- ⑥ 4.5 inch Half metal body
- ⑦ IP66

MODEL	CTP-AFHD-4520XR	CTP-AFHD-4530XR
Sensor	SONY STARVIS SENSOR	
Effective pixels	1080P 1920 (H) X 1080 (V)	
Total pixels	2.0MP	
Zoom	20X optical zoom	36X optical zoom
Lens	f= 4.7mm~94mm	f= 4.6mm~165mm
Iris	F1.6 ~ F3.0	
FOV	Far end:68.5 Near end:4.2	
Min. illumination	0.01Lux / 0.00Lux[LEDs ON]	
BLC	Support	
WB	Indoor/Outdoor/Auto/Manual	
D/N	IR-CUT	
S/N Ratio	≥50dB	
Pan range	360°continuous rotation	
Tilt range	93°	
Auto Flip	Horizontal 180°;Vertical 93°	
Manual Pan speed	0.1°- 80°/s	
Manual Tilt speed	0.1°- 40°/s	
Preset Points	220	
Guard Tours	3 groups	
A-B Scan	User programmable	
A-B Scan Speed	01 ~ 9 Level	
Dwell Preset	01-60s interval available	
Guard Points	Max.16 points, dwell time user selectable	
Operating temperature	Indoor:0°C ~ +40°C Outdoor: -40°C ~ +60°C	
Operation menu	English	
Pan and Tilt position display	Support	
Humidity	≤95% Non Condensing	
Power	DC12V 2A	
Consumption	≤ 20W	
Lightning Protection	Transient voltage 6000V	
Video interface output	AHD / TVI / CVI / CVBS	
Communication mode	RS485 (+/-) / Coaxial cable	
Related validation	KC, CE, FCC, RoHs	
Auto Control IR LED	PWM	
LEDs	6 pcs	
IR distance	Up to 80 meters	
Support ambient light detection	IR illumination on 1-15 grades selectable;	