

Item			5MP AHD / TVI / CVI / 960H / IP Hybrid DVR (w/ sensor alarm)		
					
모델명			IQ-QH04	IQ-QH08	IQ-QH16
Video Input Format			AHD,TVI(up to 5MP), CVI (up to 4MP), 960H, IP		
Video & Audio					
Video System			NTSC/PAL		
Video Input	BNC	4 inputs		8 inputs	16 inputs
	BNC & IP	Up to 6 Channels (BNC x4 + IP x2)		Up to 12 Channels (BNC x8 + IP x4)	Up to 24 Channels (BNC x16 + IP x8)
	IP Only	6 inputs		12 inputs	8 inputs
Video Output			1 VGA(up to 1080P) and 1 HDMI(4CH 1080P, 8CH & 16CH up to 4K) output		
Audio input / output (RCA)			4 inputs / 1 output	8 inputs / 1 output	16 inputs / 1 output
Recording					
Video Compression			H.264		
Analog	Recroding Resoluitiion		2592X1944(5MP), 2592x1520(4MP), 2048x1536(3MP), 1920x1080(1080P), 1280x720(720P), 960x480(960H)		
	Recoding Frame Rate While in Live View (Per Channel)	5MP	PAL/NTSC: 10fps	PAL/NTSC: 12fps	PAL/NTSC: 11fps
		4MP	PAL/NTSC: 15fps		
		3MP	PAL/NTSC: 20fps		
		2MP(1080P)	PAL: 25fps / NTSC: 30fps		
		1MP(720P)	PAL: 25fps / NTSC: 30fps		
		960H	PAL: 25fps / NSTC: 30fps		
IP	IP Camera Support		4MP / 3MP / 2MP(1080P) / 1M(720P) / 960H		
	Recoding Frame Rate		(Per Channel) PAL:25fps NTSC: 30fps		
	Input Bandwidth		16Mbps~48Mbps	32Mbps~96Mbps	64Mbps
	Max. Output Bandwidth		32Mbps	64Mbps	128Mbps
	Peak Decode Performance		2CHs realtime @4MP 4CHs realtime @1080P	4CHs realtime @4MP 8CHs realtime @1080P	8CHs realtime @4MP 16CHs realtime @1080P
Recording Mode			Continuous / Manual / Schedule / Motion Detection / Sensor Triggered		
HDD Supported			1 SATA HDD, up to 6TB	2 SATA HDDs, up to 12TB	2 SATA HDDs, up to 12TB
Network					
Network Interface			RJ45, 10M/100M		
Network Type			Static IP, DHCP, PPPoE, 3G		
DDNS Support			Yes		
Web Surveillance Support			IE / Firefox / Google Chrome / Mac Safari		
Mobile App Support			iOS & Android APP: RxCamView		
Playback & Backup					
Local Playback Simultaneously			Max. 4 Channels	Max. 8 Channels	Max. 16 Channels
Remote Playback via Network			Max. 4 Channels Simultaneously via CMS, IE/Mac Safari or Mobile App		
Playback Search			Date & Time / Event List / Picture / Smart Search		
Backup Method			USB, Network, e-SATA (Optional)		
General					
USB			USB2.0 x2	USB3.0 x1, USB2.0 x1	USB3.0 x1, USB2.0 x1
PTZ Control			Yes, built-in RS485 & Coaxial Protocol (UTC)		
Sensor & Alarm Port			4 inputs / 1 output	8 inputs / 1 output	16 inputs / 1 output
Power Supply			DC 12V/2A	DC 12V/5A	DC 12V/5A
Dimension(WxDxH)			300X227X53mm	378x340x50mm	378x340x50mm
Working Environment			-10°C~+55°C / 10%~90%RH		