

IQ-402HL / 802HL / 1604HL

아날로그 DVR

960H DVR ::



◀ IQ-402HL
IQ-802HL



IQ-1604HL ▶



제품특징

- 아날로그 DVR
- 1280x1024 Display
- H.264 Codec
- 4채널:120fps@CIF
- 8채널:240fps@CIF
- 16채널:480fps@CIF
- 1SATA HDD
- 스마트폰 원격뷰어(MPRMS)

주요사양

모델		IQ-402HL	IQ-802HL	IQ-1604HL
Operationg 시스템		Embedded Linux		
영상 압축		H.264		
음성 압축		G723.1		
영상 Standard		NTSC / PAL		
영상	입력	4채널	8채널	16채널
	출력	Composite (1), VGA (1)		
	해상도	Max. 1280 x 1024		
	디스플레이 모드	TV, CCTV, VGA Monitor (Selectable)		
Live		Real Time View		
화면 분할모드		1, 4	1, 4, 6, 8, 9	1, 4, 6, 8, 9, 10, 13, 16
녹화 해상도	NTSC	CIF(352×240), 2CIF(704×240), D1(704×480)		
	PAL	CIF(352×288), 2CIF(704×288), D1(704×576)		
녹화 속도	CIF(NTSC/PAL)	120 / 100 fps	240 / 225 fps	480 / 400 fps
	2CIF(NTSC/PAL)	60 / 50 fps	120 / 100 fps	240 / 200 fps
	D1(NTSC/PAL)	30 / 25 fps	60 / 50 fps	120 / 100 fps
녹화 모드		Emergency, Schedule, 센서, Motion,센서+Motion, Pre & post 알람 녹화		
검색	Mode	Calendar, Date & Time, Event Search, First Search, Last Search		
	속도	x1, x2, x4, x8, x10		
음성	In / Out	4/1		
	Volume	Adjustable		
센서 입력 / 알람 출력		4/1		
Port	Rs-232	External Keyboard Controller & PTZ		
	Rs-485			
	TCP-IP	10/100/1000 Base-Tx Ethernet (RJ-45) – 고정IP, DHCP & DDNS		
네트워크 Transmission		영상 Dual Stream (Local 녹화 & 네트워크 Transmission)		
Remote Management (IE)		CMS, Web Monitoring		
백업 Device	Internal	ODD 백업 (옵션al)		
	External	Local 백업 [USB 메모리 and 네트워크 백업 by CMS & Web browser]		
HDD		1 x SATA HDD & USB HDD		
시스템 Operation		Front Button, USB Mouse, IR Remote Controller, External Ketboard		
Etc	Multi Language			
	PTZ control by Virtual Joystick(operated by mouse)			
	백업 Viewer Auto Copy & AVI Export			
전원		12VDC 5A Adaptor		
Operation Temp.		0℃ ~ 40℃		
외형치수		300mm (w) x 64mm (h) x 220mm (d)		
무게		3.5Kg		

외관도

단위:mm

