

IQ-412SDI

HD 4채널 DVR

Full HD

HD DVR ::



제품특징

- Full HD 1080p
- 4채널
- 1920x1080p HDMI Display
- H.264 Codec
- 4채널:120fps@1080p
- 3SATA HDD
- 스마트폰 원격뷰어(MPRMS)

주요사양

모델	IQ-412SDI	
타입	SDI only	
작동OS	Embedded Linux	
영상압축	H.264	
음성압축	G723.1	
영상신호	NTSC / PAL	
영상	입력	4Ch
	출력	HDMI, VGA, CVBS, SPOT
	해상도(HD)	1920X1080, 1280X720
라이브	Realtime	
분할모드	1, 4	
녹화해상도	1920*1080, 1920*540, 960*540, 1280*720, 1280*360, 640*360	
녹화속도	120fps@1080p	
녹화모드	Continuous, Schedule, Alarm, Motion, Emergency	
검색	모드	Calendar, Date&Time, Event Search, First Search, Last Search, Backup Search
	속도	x1, x2, x4, x8, x16
음성	입/출력	4 / 1
센서 입력/ 알람 출력	4 / 1	
포트	RS-232	External Keyboard controller & PTZ
	RS-485	
	LAN	10/100/1000 Base-Tx Ethernet (RJ-45) - Fixed IP, DHCP & DDNS
Network Transmission	Video Dual-Stream (Local recording & Network Transmission)	
원격제어	Built-in Web server (IE browser), iPhone, Android,	
백업장비	Local Backup by USB Memory Stick and Network Backup by CMS	
HDD	3 HDD, 1 eSATA	
기타	Multi-Language	
	PTZ control by virtual joystick(operated by mouse)	
	Viewer auto copy & AVI export	
전원	Adaptor 12V 6.67A (당 항목은 변경될 수 있음)	
작동온도	0°C ~ 40°C	
소비전력	34.7W	
외형치수	430 mm(W) X 88mm(H) X 481mm(D)	
무게	4.1kg	

외관도

단위:mm

