







썬치라이트
IR Bullet
500K



▼ SPECIFICATION

- 500k / 5~50mm / 썬치라이트 60LED / 펄 10 + IR 50LED / 650TVL /
- 1/3 INCH SONY SUPER HAD CCD II
- HIGH RESOLUTION / HIGH SENSITIVITY 650TVL
- WATERPROOF (IP68) / TRUE DAY AND NIGHT (ICR)
- 0 Lux at IR (M10/50 WHITE 60)
- D-WDR (DIGITAL WIDE DYNAMIC RANGE) / FUNCTION
- 3DDNR (3D DIGITAL NOISE REDUCTION) / LSC
- SMART MOTION DETECTION / PRIVACY

▼ DIMENSION



▼ SPECIFICATION

HD CCTV DVR
www.iseeq.co.kr

Specification	IQ-SIL120FV
Resolution	650 TV LINES
Sensor	1/3 INCH SONY SUPER HAD CCD II
Total Pixels	811(H) x 508(V) 410K pixels (NTSC) / 795(H) x 595(V) 470K pixels (PAL)
Effective Pixels	768(H) x 494(V) 380K pixels (NTSC) / 752(H) x 582(V) 440K pixels (PAL)
Scanning System	2:1 Interlace
S/N (Y signal)	More than 52 dB (AGC OFF)
Frequency	Horizontal:15.734KHz / Vertical:59.94Hz (NTSC) Horizontal:15.625KHz / Vertical:50.00Hz (PAL)
Video Output	CVBS: 1.0Vp-p / 75ohm
Min.Illumination	0 Lux at IR On
Electronic shutter speed	AUTO / MANUAL (1/60sec~1/100,000sec) (NTSC) AUTO / MANUAL (1/50sec~1/100,000sec) (PAL)
O.S.D	Built-in (Option : OSD cable controlled)
White Balance	ATW / PUSH / MANUAL Adjustable
Backlight Compensation	OFF / BLC / HLC / HBLG
AGC (Auto Gain Control)	OFF / LOW MIDDLE HIGH Selectable
D-WDR	ON / OFF
3DDNR	OFF / LOW / MIDDLE / HIGH / AUTO
Day & Night	AUTO (Day <=> Night time Change) / EXT / COLOR / B/W
Smart IR	OFF / ON
Privacy	OFF / ON (8 Zone)
Smart Motion Detection	OFF / ON (4 Zone)
Image Conversion	OFF / ON
LSC	OFF / ON
SHARPNESS	ADJUSTABLE
Operating Temperature/Humidity	-10°C ~ +40°C / 30% ~ 80% RH
Storage Temperature/Humidity	-20°C ~ +60°C / 20% ~ 90% RH
Power	DC12V [AC24V / DC12V DualPower (option)]
Lens	DC Auto IRIS V/F 5~50mm