

IQHD-72H8V

Hi-power IR LED 210만화소 HD-SDI Camera

Full HD




제품특징

- 1/2.9 inch SONY CMOS (IMX-222) / HD-SDI (1080P, 720P, 720P CROP)
- High Definition Serial Digital Interface / 0 Lux at IR On (Hi-power LED 12 pcs)
- Upgraded Waterproof Housing (IP68rating) / OSD Controlled / DNR (Digital Noise Reduction)
- Smart IR / WDR (Wide Dynamic Range) / Day & Night (ICR Option) / D.ZOOM
- Privacy / Image Conversion / Easy Installation / 3Axis Concealed Bracket
- DC Auto IRIS & TDN V/F Lens 2.8~12mm

외관도

단위:mm



주요사양

모델	IQHD-72H8V
해상도	1080P, 720P, 720P CROP
이미지센서	1/2.9 inch SONY CMOS (IMX-222)
총화소	2000(H) x 1241(V) = 2,482,000
유효화소	1944(H) X 1092(V) = 2,122,648
스캐닝 시스템	PROGRESSIVE
S/N (Y signal)	More than 52 dB (AGC Off)
영상 출력	SMPTE292M (HD-SDI) / (CVBS: 1.0Vp-p (75ohm) : Option)
최저조도	0 Lux at IR On (Hi-power LED 8pcs)
화이트บาล런스	AUTO / AUTO EXT / PRESET / MANUAL
전자셔터	AUTO / MANUAL (1/30sec ~ 1/60,000sec)
밝기	ADJUSTABLE (0 ~ 20 STEP)
센스업	OFF / X2 / X3 / X4 / X5 / X6 / X7 / X8
DNR	OFF / LOW / MIDDLE / HIGH
BACKLIGHT	OFF / WDR / BLC / HLM
ACE	OFF / LOW / MIDDLE / HIGH
Day & Night	AUTO (Day <--> Night TIME Change) , COLOR , B/W, EXTERN, MDIR (SEARCH Option)
사생활보호	OFF / ON (16 Zone)
모션감지	OFF / SET
디지털줌	0 ~ 127
플립	OFF / ON
FREEZE	OFF / ON
언어	ENG, CHN, CHN(S), JPN, KOR
선명도	ADJUSTABLE (0 ~ 10 STEP)
DEFOG	OFF / SET
통신	RS-485 (PELCO-D)
SMART IR	ADJUSTABLE (0 ~ 20 STEP)
작동환경	-10'C ~ +50'C / 30%~80% RH
보관환경	-20'C ~ +60'C / 20%~90% RH
전원	DC12V [AC24V / DC12V DualPower (option)]
렌즈	DC Auto IRIS & TDN V/F Lens 2.8~12mm
신호전송거리	케이블용선과 설치환경에 따라 차이가 있음(5C-HF8T기준 : 200M)