

Full HD



MX2-08M
HD 8ch / 60FPS / 2HDD
1920x1080p

▼ SPECIFICATION

8ch / 1920x1080p / 1080p 60fps / 2 HDD / H.264 / Web Viewer

▼ DIMENSION



▼ SPECIFICATION

HD CCTV DVR
www.iseeq.co.kr

Model	MX2-08M	
System	Time Accuracy	5ppm (12.5sec/month)
	Time Sync.	NTP, GMT, DST, TIME server
	User	Live monitoring, Recording, Playback, Backup, Network, Setup
Video	Input	8 BNC
	Output	1 HDMI, 1 VGA, 1 BNC
	Loop	N/A
	Spot	N/A
Audio	Input	4 RCA
	Output	1 HDMI, 1 RCA
VideoRecording	Speed	1080p 60fps
	Resolution	1920x1080p
	Quality	5 Levels
	Bit Rate	664kbps ~ 7Mbps/Ch, Adjustable
AudioRecording	Compression	G.726
	Interface	10/100/1G
Network	Compression	H.264 or JPEG
	Speed	1080p 10fps
	Resolution	1920x1080p
	Pre/Post-Alarm	5sec / 5sec~5min
Alarm	Motion Grid	16x12 (NTSC/PAL)
	Alarm Action	E-mail, Channel Popup, Buzzer, Relay, PTZ Preset, Remote CMS
	Input / Output	4/1 - NC/NO
	HDMI	Full HD, HD, XGA
Display	VGA	Full HD, HD, XGA
	TV	SDTV (720x480/576)
	PTZ / Keyboard	2 RS485 - Terminal Block
ExternalInterface	ATM / POS	RS232C - Terminal Block
	Storage	2 HDD, 1 eSATA
General	OS	Embedded Linux
	Compression	H.264
	Power Supply	12V/5A - Level 5
	Consumption	60/40Watts
	Operating Temp	5 ~ 40°C
	Humidity	10 ~ 80%
	Net Weighr (w/o HDD)	3Kg
	Certification	CE, FCC, RoHS Compliance